SAFETY DATA SHEET



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name Castrol GTX 0W-20 RN17 FE

Product code 470922-DE01 SDS# 470922 **Product type** Liquid.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/

Engine Oils.

mixture

For specific application advice see appropriate Technical Data Sheet or consult our company

representative.

1.3 Details of the supplier of the safety data sheet

Supplier Castrol Holdings Europe B.V.,

d'Arcyweg 76, 3198NA

Europoort Rotterdam

BP Italia S.p.A.

Sede Legale via G.De Castillia 23

20124 Milano (Mi), Italia

+39 (0)800 906347

E-mail address MSDSadvice@bp.com

1.4 Emergency telephone number

EMERGENCY

TELEPHONE NUMBER

Italy Poison Center

Carechem: +44 (0) 1235 239 670 (24/7)

1. CAV, Azienda ospedaliera "Antonio Cardarelli", III Servizio di anestesia e rianimazione, via

Antonio Cardarelli 9, Napoli - Tel: 081-5453333;

2. CAV, Azienda ospedaliera universitaria Careggi, U.O. Tossicologia medica, via Largo

Brambilla 3, Firenze - Tel: 055-7947819;

3. CAV, Centro nazionale d'informazione tossicologica, IRCCS Fondazione Salvatore Maugeri Clinica del lavoro e della riabilitazione, via Salvatore Maugeri 10, Pavia - Tel: 0382-24444; 4. CAV, Azienda ospedaliera Niguarda Ca' Grande, piazza Ospedale Maggiore 3, Milano -Tel:

02-66101029;

5. CAV. Azienda ospedaliera "Papa Giovanni XXIII", tossicologia clinica, Dipartimento di

farmacia clinica e farmacologia, piazza OMS 1, Bergamo- Tel: 800883300;

6. CAV "Umberto I", PRGM tossicologia d'urgenza, viale del Policlinico 155, Roma – Tel: 06-49978000;

7. CAV del Policlinico "Agostino Gemelli", Servizio di tossicologia clinica, largo Agostino

Gemelli 8, Roma- Tel: 06-3054343;

8. CAV, Azienda ospedaliera universitaria riuniti, viale Luigi Pinto 1, Foggia- Tel: 800183459;

9. CAV, Ospedale pediatrico Bambino Gesù, Dipartimento emergenza e accettazione DEA,

piazza Sant'Onofrio 4, Roma - Tel: 06 68593726;

10. CAV dell'Azienda ospedaliera universitaria integrata (AOUI) di Verona sede di Borgo

Trento, piazzale Aristide Stefani, 1 - 37126 Verona -Tel: 800011858.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

See sections 11 and 12 for more detailed information on health effects and symptoms and environmental hazards.

2.2 Label elements

Signal word No signal word.

Product name Castrol GTX 0W-20 RN17 FE Product code 470922-DE01 Page: 1/12

Date of issue 4 July 2024 Language ENGLISH Version 3 Format Italy

(Italy) 2 April 2024. Date of previous issue

SECTION 2: Hazards identification

Hazard statements No known significant effects or critical hazards.

Precautionary statements

PreventionNot applicable.ResponseNot applicable.StorageNot applicable.DisposalNot applicable.Hazardous ingredientsNot applicable.

Supplemental label

Contains C14-16-18 Alkyl phenol. May produce an allergic reaction.

elements Safety data sheet available on request.

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant

Not applicable.

fastenings

Tactile warning of danger Not applicable.

2.3 Other hazards

Results of PBT and vPvB assessment

Product does not meet the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006,

Annex XIII.

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification

Defatting to the skin. USED ENGINE OILS

Used engine oil may contain hazardous components which have the potential to cause skin

cancer.

See Toxicological Information, section 11 of this Safety Data Sheet.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Product definition Mixture

Highly refined base oil (IP 346 DMSO extract < 3%). Synthetic base stock. Proprietary performance additives.

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Sistillates (petroleum), hydrotreated heavy paraffinic	REACH #: 01-2119484627-25 EC: 265-157-1 CAS: 64742-54-7 Index: 649-467-00-8	≥50 - ≤75	Asp. Tox. 1, H304	-	[1]
Dec-1-ene, trimers, hydrogenated	REACH #: 01-2119486452-34 EC: 500-393-3 CAS: 157707-86-3	≤10	Asp. Tox. 1, H304	-	[1]
Dec-1-ene, trimers, hydrogenated	REACH #: 01-2119493949-12 EC: 500-393-3 CAS: 157707-86-3	≤10	Asp. Tox. 1, H304	-	[1]
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	REACH #: 01-2119474878-16 EC: 276-737-9 CAS: 72623-86-0 Index: 649-482-00-X	≤5	Asp. Tox. 1, H304	-	[1]
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	REACH #: 01-2119474889-13 EC: 276-738-4 CAS: 72623-87-1	≤5	Asp. Tox. 1, H304	-	[1]

Product name C	Castrol GTX 0V	V-20 RN17 FE		Product code 470922-	DE01	Page: 2/12
Version 3	Date of issue	4 July 2024	Format	Italy	Language	ENGLISH
Date of previo	us issue	2 April 2024.		(Italy)		

SECTION 3: Composition/information on ingredients

Index: 649-483-00-5

bis(nonylphenyl)amine REACH #: ≤3 Aquatic Chronic 4, H413 - [1]

01-2119488911-28 EC: 253-249-4

CAS: 36878-20-3

C14-16-18 Alkyl phenol REACH #: <1 Skin Sens. 1B, H317 - [1]

01-2119498288-19 STOT RE 2, H373

See Section 16 for the full text of the H statements declared above.

Type

[1] Substance classified with a health or environmental hazard Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids

should be held away from the eyeball to ensure thorough rinsing. Check for and remove any

contact lenses. Get medical attention.

Skin contact Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove

contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before

reuse. Get medical attention if irritation develops.

Inhalation If inhaled, remove to fresh air. In case of inhalation of decomposition products in a fire,

symptoms may be delayed. The exposed person may need to be kept under medical

surveillance for 48 hours. Get medical attention if symptoms occur.

Ingestion Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if

symptoms occur.

Protection of first-aidersNo action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Potential acute health effects

Inhalation Exposure to decomposition products may cause a health hazard. Serious effects may be

delayed following exposure.

Ingestion No known significant effects or critical hazards.

Skin contact Defatting to the skin. May cause skin dryness and irritation.

Eye contact No known significant effects or critical hazards.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the

respiratory tract.

Ingestion Ingestion of large quantities may cause nausea and diarrhoea.

Skin contact Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.

Eye contact Potential risk of transient stinging or redness if accidental eye contact occurs.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physicianTreatment should in general be symptomatic and directed to relieving any effects.

In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.

media

Unsuitable extinguishing

media

Do not use water jet. The use of a water jet may cause the fire to spread by splashing the

burning product.

5.2 Special hazards arising from the substance or mixture

Hazards from theIn a fire or if heated, a pressure increase will occur and the container may burst.

substance or mixture

Hazardous combustion Combustion products may include the following:

products

carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide)

nitrogen oxides (NO, NO2 etc.)

Product nameCastrol GTX 0W-20 RN17 FEProduct code470922-DE01Page: 3/12Version 3Date of issue 4 July 2024FormatItalyLanguageENGLISH

Date of previous issue 2 April 2024. (Italy)

SECTION 5: Firefighting measures

5.3 Advice for firefighters

Special precautions for fire-fighters

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Floors may be slippery; use care to avoid falling. Put on

appropriate personal protective equipment.

If specialised clothing is required to deal with the spillage, take note of any information in For emergency responders Section 8 on suitable and unsuitable materials. See also the information in "For non-

emergency personnel".

6.2 Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

Small spill Stop leak if without risk. Move containers from spill area. Absorb with an inert material and

place in an appropriate waste disposal container. Dispose of via a licensed waste disposal

contractor.

Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water Large spill

courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other

sections

See Section 1 for emergency contact information.

See Section 5 for firefighting measures.

See Section 8 for information on appropriate personal protective equipment.

See Section 12 for environmental precautions.

See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment.

Eating, drinking and smoking should be prohibited in areas where this material is handled, Advice on general occupational hygiene stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional

information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep away from heat and direct sunlight. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store and use only in equipment/ containers designed for use with this product. Do not store in unlabelled containers.

Prolonged exposure to elevated temperature

7.3 Specific end use(s)

Not suitable

Recommendations See section 1.2 and Exposure scenarios in annex, if applicable.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapour or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Product name Castrol GTX 0W-20 RN17 FE Product code 470922-DE01 Page: 4/12 Language ENGLISH Version 3 Date of issue 4 July 2024 Format Italy (Italy) 2 April 2024. Date of previous issue

SECTION 8: Exposure controls/personal protection

Recommended monitoring procedures

Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Biological exposure indices

Product/ingredient name

Exposure indices

No exposure indices known.

Derived No Effect Level

No DNELs/DMELs available.

Predicted No Effect Concentration

No PNECs available

8.2 Exposure controls

Appropriate engineering controls

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Eye/face protection Skin protection Safety glasses with side shields.

Skin protection

Hand protection

protection General Information:

Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. The correct choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. Most gloves provide protection for only a limited time before they must be discarded and replaced (even the best chemically resistant gloves will break down after repeated chemical exposures).

Gloves should be chosen in consultation with the supplier / manufacturer and taking account of a full assessment of the working conditions.

Recommended: Nitrile gloves.

Breakthrough time:

Breakthrough time data are generated by glove manufacturers under laboratory test conditions and represent how long a glove can be expected to provide effective permeation resistance. It is important when following breakthrough time recommendations that actual workplace conditions are taken into account. Always consult with your glove supplier for up-to-date technical information on breakthrough times for the recommended glove type.

Our recommendations on the selection of gloves are as follows:

Continuous contact:

Gloves with a minimum breakthrough time of 240 minutes, or >480 minutes if suitable gloves can be obtained.

Product nameCastrol GTX 0W-20 RN17 FEProduct code470922-DE01Page: 5/12Version 3Date of issue 4 July 2024FormatItalyLanguageENGLISHDate of previous issue2 April 2024.(Italy)

SECTION 8: Exposure controls/personal protection

If suitable gloves are not available to offer that level of protection, gloves with shorter breakthrough times may be acceptable as long as appropriate glove maintenance and replacement regimes are determined and adhered to.

Short-term / splash protection:

Recommended breakthrough times as above.

It is recognised that for short-term, transient exposures, gloves with shorter breakthrough times may commonly be used. Therefore, appropriate maintenance and replacement regimes must be determined and rigorously followed.

Glove Thickness:

For general applications, we recommend gloves with a thickness typically greater than 0.35 mm.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times. Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

- Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
- Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential.

Skin and body

Use of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Refer to standards:

Respiratory protection: EN 529 Gloves: EN 420, EN 374 Eye protection: EN 166 Filtering half-mask: EN 149 Filtering half-mask with valve: EN 405

Half-mask: EN 140 plus filter Full-face mask: EN 136 plus filter Particulate filters: EN 143 Gas/combined filters: EN 14387

Environmental exposure

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Physical state

Colour

Amber.

Odour

Not available.

Odour threshold

Melting point/freezing point

Initial boiling point and boiling range

Liquid.

Amber.

Not available.

Not available.

Not available.

Product nameCastrol GTX 0W-20 RN17 FEProduct code470922-DE01Page: 6/12Version 3Date of issue 4 July 2024FormatItalyLanguageENGLISH

Date of previous issue 2 April 2024. (Italy)

SECTION 9: Physical and chemical properties

Flammability
Lower and upper explosion

limit

Not available.

Flash point Closed cup: 210°C (410°F) [Pensky-Martens ASTM D 93]

Open cup: 233°C (451.4°F) [Cleveland DIN EN ISO 2592]

Auto-ignition temperature

Ingredient name

°C

°F

Method

Dec-1-ene, homopolymer, hydrogenated

Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated

bis(nonylphenyl)amine

°C

°F

Method

649.4 to 696.2 ASTM D 2159

Decomposition temperature

pН

Not available.

Not applicable.

Kinematic viscosity

Kinematic: 38.17 mm²/s (38.17 cSt) at 40°C Kinematic: 7.8 to 9.2 mm²/s (7.8 to 9.2 cSt) at 100°C

Solubility

Media	Result
water	Not soluble

Partition coefficient n-octanol/ water (log value)

Vapour pressure

Not applicable.

	Vapour Pressur		re at 20°C Vapo		our pressure at 50°C	
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
Stillates (petroleum), hydrotreated heavy paraffinic	<0.07501	<0.01	ASTM D 5191			
Dec-1-ene, homopolymer, hydrogenated	<0.0041	<0.00055	ASTM E 1194-87			
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil- based	<0.07501	<0.01	ASTM D 5191			
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil- based	<0.07501	<0.01	ASTM D 5191			
bis(nonylphenyl)amine	<0.01	<0.0013	EU A.4	0.0019	0.00025	EU A.4

Density and/or Relative density

Relative vapour density

<1000 kg/m³ (<1 g/cm³) at 15°C Not available.

Particle characteristics

Median particle size

cle size Not applicable.

9.2 Other information

Evaporation rate

Explosive properties

Oxidising properties

Pour point

Not available.

Not available.

-45 °C

SECTION 10: Stability and reactivity

10.1 ReactivityNo specific test data available for this product. Refer to Conditions to avoid and Incompatible

materials for additional information.

10.2 Chemical stability The product is stable.

10.3 Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.

10.4 Conditions to avoid Avoid all possible sources of ignition (spark or flame).

Product nameCastrol GTX 0W-20 RN17 FEProduct code470922-DE01Page: 7/12Version 3Date of issue 4 July 2024FormatItalyLanguageENGLISHDate of previous issue2 April 2024.(Italy)

SECTION 10: Stability and reactivity

10.5 Incompatible materials Reactive or incompatible with the following materials: oxidising materials.

10.6 Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be

produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	(vapours)	
Long chain alkyl phenol	2500	N/A	N/A	N/A	N/A

Aspiration hazard

Product/ingredient name	Result
Distillates (petroleum), hydrotreated heavy paraffinic	ASPIRATION HAZARD - Category 1
Dec-1-ene, homopolymer, hydrogenated	ASPIRATION HAZARD - Category 1
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	ASPIRATION HAZARD - Category 1
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	ASPIRATION HAZARD - Category 1
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	ASPIRATION HAZARD - Category 1

Conclusion/Summary Not classified. Based on available data, the classification criteria are not met.

Information on likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Potential acute health effects

Inhalation Exposure to decomposition products may cause a health hazard. Serious effects may be

delayed following exposure.

Ingestion No known significant effects or critical hazards.

Skin contact Defatting to the skin. May cause skin dryness and irritation.

Eye contact No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

InhalationNo specific data.IngestionNo specific data.

Skin contact Adverse symptoms may include the following:

irritation dryness cracking

Eye contact No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the

respiratory tract.

Ingestion Ingestion of large quantities may cause nausea and diarrhoea.

Skin contact Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.

Eye contact Potential risk of transient stinging or redness if accidental eye contact occurs.

Potential chronic health effects

General USED ENGINE OILS

Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.

CarcinogenicityNo known significant effects or critical hazards.MutagenicityNo known significant effects or critical hazards.Developmental effectsNo known significant effects or critical hazards.Fertility effectsNo known significant effects or critical hazards.

Product nameCastrol GTX 0W-20 RN17 FEProduct code470922-DE01Page: 8/12Version 3Date of issue 4 July 2024FormatItalyLanguageENGLISH

Date of previous issue 2 April 2024. (Italy)

SECTION 11: Toxicological information

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

Remarks - Endocrine disrupting properties for human health Conclusion/

Summary

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Environmental hazards Not classified as dangerous

12.2 Persistence and degradability

Not expected to be rapidly degradable.

12.3 Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

Not available

12.4 Mobility in soil

Soil/water partition

Not available.

coefficient (Koc)

Mobility Spillages may penetrate the soil causing ground water contamination.

12.5 Results of PBT and vPvB assessment

Product does not meet the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII.

12.6 Endocrine disrupting

properties

Not available.

Not available.

Remarks - Endocrine disrupting properties for

environment Conclusion/

Summary

Other ecological information Spills may form a film on water surfaces causing physical damage to organisms. Oxygen

transfer could also be impaired.

12.7 Other adverse effects No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal Where possible, arrange for product to be recycled. Dispose of via an authorised person/

licensed waste disposal contractor in accordance with local regulations.

Hazardous waste European waste catalogue (EWC)

Waste code	Waste designation	
13 02 08*	other engine, gear and lubricating oils	

However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative waste disposal code to be assigned by the end user.

Packaging

Methods of disposal Where possible, arrange for product to be recycled. Dispose of via an authorised person/

licensed waste disposal contractor in accordance with local regulations.

Special precautions This material and its container must be disposed of in a safe way. Empty containers or liners

may retain some product residues. Avoid dispersal of spilt material and runoff and contact with

soil, waterways, drains and sewers.

References Commission 2014/955/EU

Directive 2008/98/EC

Product name Castrol GTX 0W-20 RN17 FE Product code 470922-DE01 Page: 9/12 Language ENGLISH Version 3 Date of issue 4 July 2024 Format Italy (Italy) 2 April 2024. Date of previous issue

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

14.6 Special precautions for

Not available.

user

instruments

14.7 Maritime transport in bulk according to IMO

Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
Ø yclohexane	<0.01	57 [Neoprene-based contact adhesive]
nickel	<0.0001	27
lead powder [particle diameter < 1 mm]	< 0.0001	72

Labelling Not applicable.

Other regulations

REACH Status The company, as identified in Section 1, sells this product in the EU in compliance with the

current requirements of REACH.

United States inventory

(TSCA 8b)

All components are active or exempted.

Australia inventory (AllC)
Canada inventory
China inventory (IECSC)
All components are listed or exempted.

(PICCS)

All components are listed or exempted.

Substances Inventory

Taiwan Chemical

(TCSI)

ntory

Explosive precursors Mot applicable.

Ozone depleting substances (1005/2009/EU)

Product nameCastrol GTX 0W-20 RN17 FEProduct code470922-DE01Page: 10/12Version 3Date of issue 4 July 2024FormatItalyLanguageENGLISHDate of previous issue2 April 2024.(Italy)

SECTION 15: Regulatory information

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

EU - Water framework directive - Priority substances

None of the components are listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for one or more of the substances within this mixture. A Chemical Safety Assessment has not been carried out for the mixture itself.

SECTION 16: Other information

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation

[Regulation (EC) No. 1907/2006]

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SADT = Self-Accelerating Decomposition Temperature

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVCB = Complex hydrocarbon substance

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Varies = may contain one or more of the following 64741-88-4 / RRN 01-2119488706-23,

64741-89-5 / RRN 01-2119487067-30, 64741-95-3 / RRN 01-2119487081-40, 64741-96-4/ RRN

01-2119483621-38, 64742-01-4 / RRN 01-2119488707-21, 64742-44-5 / RRN

01-2119985177-24, 64742-45-6, 64742-52-5 / RRN 01-2119467170-45, 64742-53-6 / RRN

01-2119480375-34, 64742-54-7 / RRN 01-2119484627-25, 64742-55-8 / RRN

01-2119487077-29, 64742-56-9 / RRN 01-2119480132-48, 64742-57-0 / RRN

01-2119489287-22, 64742-58-1, 64742-62-7 / RRN 01-2119480472-38, 64742-63-8,

64742-65-0 / RRN 01-2119471299-27, 64742-70-7 / RRN 01-2119487080-42, 72623-85-9 / PPN 01-2119555262-43, 72623-86-0 / PPN 01-2119474878-16, 72623-87-1 / PPN

RRN 01-2119555262-43, 72623-86-0 / RRN 01-2119474878-16, 72623-87-1 / RRN

01-2119474889-13

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Product nameCastrol GTX 0W-20 RN17 FEProduct code470922-DE01Page: 11/12Version 3Date of issue 4 July 2024FormatItalyLanguageENGLISHDate of previous issue2 April 2024.(Italy)

SECTION 16: Other information				
Classifi	ication	Justification		
Not classified.				
Full text of abbreviated H statements	H304 H317 H373	May be fatal if swallowed and enters airways. May cause an allergic skin reaction. May cause damage to organs through prolonged or repeated exposure. May cause long lasting harmful effects to aquatic life.		
Full text of classifications [CLP/GHS]	Aquatic Chronic 4 Asp. Tox. 1 Skin Sens. 1B STOT RE 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4 ASPIRATION HAZARD - Category 1 SKIN SENSITISATION - Category 1B SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2		
<u>History</u>				
Date of issue/ Date of revision	04/07/2024.			
Date of previous issue	02/04/2024.			
Prepared by	Product Stewardship			

▼ Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product nameCastrol GTX 0W-20 RN17 FEProduct code470922-DE01Page: 12/12Version 3Date of issue 4 July 2024FormatItalyLanguageENGLISHDate of previous issue2 April 2024.(Italy)